








PRODUCT COMPARISON

<p>1664</p> 	<p>1674</p> 	<p>1670</p> 	<p>1673</p> 	<p>1678</p> 
5 km Range (LOS)	8 km Range (LOS)	5-8 km Range (LOS)	5-8 km Range (LOS)	8-20 km Range (LOS)
1 Remote Capability	2 Remote Capability	8 Remote Capability	64 Remote Capability	8 Remote Capability
Dual Output Remote	Non-Electric Remotes	Dual & Non-Electric Remotes	Dual Remotes	Electric or Non-Electric Remotes
Water Resistant	Water Submersible	Water Resistant	Water Resistant	Water Submersible (100ft.)
Rechargeable NiCad	Rechargeable NiMH	Rechargeable NiMH	Rechargeable NiMH	Rechargeable NiMH
7 hr. Battery Standby	16 hr. Battery Standby	10-12 hr. Battery Standby	10-14 hr. Battery Standby	200-300 hr. Battery Standby
5W Controller / 2W Remote	5W Controller / 5W Remote	5W Controller / 2 or 5W Remote	5W Controller / 2W Remote	5W Controller / 2 or 5W Remote
17.25lb Controller / 7.25lb Remote	6lb Controller / 6.25lb Remote	6.5lb Controller / 7.25lb Remote	6.5lb Controller / 7lb Remote	2lb Controller / 1.33lbs Remote
20.5 x 17.5 x 9 in	9.25 x 7.5 x 4.5 in	10 x 12 x 4.5 in	10 x 12 x 4.5 in	6 x 3 x 3.5 in Remote
-22° to +140°F (-30° to +60°C)	-22° to +140°F (-30° to +60°C)	-22° to +140°F (-30° to +60°C)	-22° to +140°F (-30° to +60°C)	-22° to +140°F (-30° to +60°C)
		Opt. PC Display (64 Remotes)	Standby Sleep Mode	Standby Sleep Mode
		Sequential Fire	Sequential Fire	User Replaceable Battery Packs
			Adjustable Super Bright LEDs	Adjustable Super Bright LEDs
			Post Blast Motion Detection	Hard Anodized Black Aluminum
			Event Log with GPS	Small & Compact
			Retractable & Guarded Antenna	Optional Orange Covers
			LCD Display with Backlighting	Mil-Spec Standards
			Adjustable Disarm with Timer	
Proven Workhorse	Simple, Rugged & Low Cost	Versatile for both Underground and Surface Mines	All the Tools in One System	Super Rugged & Simple